




# SAFETY DATA SHEET

## 1. Identification

<b>Product Identifier</b>	<b>Float Solv</b>
<b>Other means of identification</b>	CU-8020
<b>Product code</b>	
<b>Recommended use</b>	Solvent-based floating lift station degreaser.
<b>Recommended restrictions</b>	Professional use only.
<b>Manufacturer information</b>	
<b>Company name</b>	<b>Chemical Universe, Inc.</b>
<b>Address</b>	1133 Saline St. North Kansas City, MO 64116
<b>Telephone</b>	(816) 471-3602
<b>FAX</b>	(816) 474-3302
<b>Emergency phone number</b>	PERS 24-hour Emergency (800) 633-8253

## 2. Hazard(s) Identification

<b>Physical hazards</b>	Flammable liquids	Category 3
<b>Health hazards</b>	Skin irritation	Category 2
	Eye irritation	Category 2B
	Specific target organ toxicity (Single exposure) [respiratory tract irritation]	Category 3
	Aspiration hazard	Category 1
<b>Environmental hazards</b>	Chronic exposure hazard to aquatic biota.	Category 3
<b>OSHA defined hazards</b>	None.	
<b>Label elements</b>		

**Signal word**

**DANGER**

**Hazard statement**

Flammable liquid and vapor.  
Causes skin irritation.  
Causes eye irritation.  
Suspected of causing cancer.  
May cause drowsiness or dizziness.  
May be fatal if swallowed and enters airways.

**Precautionary statement**

**Prevention**

Keep away from heat/sparks/open flames/ hot surfaces. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting/ equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/ eye protection/ face protection. Wash hands and exposed skin thoroughly after handling. Obtain special instruction before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area.

**Response**

**IF ON SKIN** (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for



# SAFETY DATA SHEET

extinction. Specific treatment: see section 4 on the Safety Data Sheet. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.

**IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention.

**IF INHALED:** Remove person to fresh air and keep comfortable breathing. Call a POISON CENTER/doctor/medical professional if you feel unwell.

**IF SWALLOWED:** Immediately call a POISON CENTER/doctor/medical professional. Do NOT induce vomiting.

**Storage**

Store in a well-ventilated place. Keep cool. Store locked up. Keep tightly closed.

**Disposal**

Dispose of contents/container in accordance with local/regional/national/international regulations.

**Hazard(s) not otherwise classified (HNOC)**

None.

**Supplemental information**

None.

### 3. Composition/information on ingredients

Mixture Component(s)		
Chemical name	CAS number	%
K-1 Kerosene	64742-81-0	>99
Other components below reportable levels		0-1

### 4. First-aid measures

**Inhalation**

Move to fresh air. Keep victim at rest in a position comfortable for breathing. Call a physician if symptoms develop or persist.

**Skin contact**

Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.

**Eye contact**

Rinse with water for at least 15 minutes. Remove contact lenses if present and easy to do so. Get medical attention if irritation develops and persists.

**Ingestion**

Rinse mouth. Get medical attention if symptoms occur. Only induce vomiting at the instruction of medical personnel.

**Most important symptoms/effects, acute and delayed**

Dermatitis. Rash. May cause an allergic skin reaction.

**Indication of immediate medical attention and special treatment needed**

Provide general support measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to the hospital. Keep victim under observation. Symptoms may be delayed.

**General information**

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

### 5. Fire-fighting measures

**Suitable extinguishing media**

Water fog. Foam. Carbon dioxide (CO<sub>2</sub>). Dry chemical powder, sand, or earth may be used for small fires only.

**Unsuitable extinguishing media**

Do not use water jet as an extinguisher, as this will spread the fire.

**Specific hazards arising from the chemical**

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source or ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable



# SAFETY DATA SHEET

mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. During fire, gases hazardous to health may be formed.

<b>Special protective equipment and precautions for firefighters</b>	Self-contained breathing apparatus and full protecting clothing must be worn in case of fire.
<b>Fire-fighting equipment/instructions</b>	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials.
<b>General fire hazards</b>	Flammable liquid and vapor.

## 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Avoid inhalation of vapors or mists. Ensure adequate ventilation. Remove all sources of ignition. State and/or local authorities should be advised if significant spillages cannot be contained or enter surface waterways. For personal protection, see section 8 of the SDS.
<b>Methods and materials for containment and cleaning up</b>	Eliminate all ignition sources. Use only non-sparking tools. Take precautionary measures against static discharge. Keep combustibles away from spilled material.  Large spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.  Small spills: Absorb with earth, sand, or other non-combustible material and transfer to container for later disposal. Clean surface thoroughly with detergent and water to remove residual contamination.  Never return spills to original container for re-use. For waste disposal, see section 13 of the SDS.
<b>Environmental precautions</b>	Avoid release to the open environment. Avoid discharge into sewers, storm drains, surface drainage paths and other areas not consistent with package labeling.

## 7. Handling and storage

<b>Precautions for safe handling</b>	Do not handle, store or open near an open flame, sources of heat or sources of ignition. Do not smoke. Use explosion proof equipment and non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
<b>Conditions for safe storage, including any incompatibilities</b>	Keep away from heat, sparks and open flame. Ground/bond container and equipment. Store in original tightly closed container. Store away from incompatible materials (see section 10 of the SDS).

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### US ACGIH Threshold Limit Values

Components	Type	Value
Kerosene (petroleum), hydro-desulfurized	TWA	200 mg/m <sup>3</sup>



# SAFETY DATA SHEET

<b>Biological limit values</b>	No information available.
<b>Appropriate engineering controls</b>	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits.
<b>Individual protection measures, such as personal protective equipment</b>	
<b>Eye/face protection</b>	Avoid contact with eyes. Wear safety glasses with side shields (or goggles).
<b>Skin protection</b>	
<b>Hand protection</b>	The use of gloves impervious to the specific material handled is advised to prevent skin contact. Users should check with manufacturers to confirm the breakthrough performance of their products. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. Suggested protective materials: Nitrile and PVC rubber.
<b>Other</b>	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.
<b>Respiratory protection</b>	In case of insufficient ventilation, wear suitable respiratory equipment.
<b>Thermal hazards</b>	Wear appropriate thermal protective clothing, when necessary.
<b>General hygiene considerations</b>	When using do not smoke or use chewing tobacco. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

## 9. Physical and chemical properties

<b>Appearance</b>	
<b>Physical State</b>	Liquid
<b>Color</b>	Colorless to light amber
<b>Odor</b>	Characteristic. Hydrocarbon/petroleum
<b>Odor threshold</b>	Not available.
<b>pH</b>	Not applicable.
<b>Melting/freezing point</b>	-4°F (-20°C).
<b>Initial boiling point and boiling range</b>	302 to 572°F (150 to 300°C).
<b>Flash point</b>	Closed cup: 100° to 140°F (38° to 60°C) [Pensky-Martens]
<b>Evaporation rate</b>	0.2 (butyl acetate=1).
<b>Flammability</b>	Not available.
<b>Flammability Limits</b>	
<b>Upper</b>	5%
<b>Lower</b>	0.7%
<b>Vapor pressure</b>	<0.27 kPa
<b>Vapor density</b>	4.5 (air=1)
<b>Specific gravity</b>	0.8 (water=1)
<b>Solubility in water</b>	Insoluble.
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	444°F (229°C).
<b>Decomposition temperature</b>	Not available.



# SAFETY DATA SHEET

Viscosity Not available.

## 10. Stability and reactivity

**Reactivity** This product is stable and non-reactive under normal conditions of use.  
**Chemical stability** Material is stable under normal conditions. Store in a cool dark place.  
**Possibility of hazardous reactions** Hazardous polymerization does not occur.  
**Conditions to avoid** Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.  
**Incompatible materials** Oxidizing agents, acids.  
**Hazardous decomposition products** Carbon dioxide, carbon monoxide.

## 11. Toxicological information

### Information on likely routes of exposure

**Ingestion** Expected to be low ingestion hazard. Do NOT induce vomiting.  
**Inhalation** Prolonged inhalation is harmful. Symptoms may include nausea or vomiting, headache, drowsiness/fatigue, dizziness/vertigo, and unconsciousness.  
**Skin contact** May cause mild skin irritation and redness.  
**Eye contact** Direct contact with eyes may cause temporary irritation.  
**Symptoms related to the physical, chemical and toxicological characteristics** Dermatitis. Rash. De-fatting of skin  
**Acute toxicity** Not established.

Product Float Solv (CAS mixture)		
Exposure Classification	Route and Species	LD <sub>50</sub> /LC <sub>50</sub>
Acute	Oral, rat	>15,500 mg/kg (literature)
Acute	Dermal, rabbit	>2,000 mg/kg estimated
Acute	Inhalation (mouse)	5.4 mg/L (92-hr) Literature
*Estimates for product may be based on additional component data not shown		

**Skin corrosion/irritation** Causes skin irritation.  
**Serious eye damage/ irritation** Causes severe eye irritation.  
**Respiratory sensitization** Not available.  
**Skin sensitization** Not available.  
**Germ cell mutagenicity** No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.  
**Carcinogenicity** One possible sub-component (naphthalene) suspected of causing cancer in female mice. Risk of cancer depends on duration and level of exposure. Naphthalene is an IARC-listed carcinogen.  
**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)** Not Listed.  
**Reproductive toxicity** This product is not expected to cause reproductive or developmental effects.  
**Specific target organ toxicity – single exposure** May cause drowsiness or dizziness.



# SAFETY DATA SHEET

Specific target organ toxicity – repeated exposure  
Aspiration hazard

Not classified.  
May be fatal if swallowed and enters airways.

## 12. Ecological information

Ecotoxicity		
Product	Float Solv (CAS mixture)	
Aquatic	Species	Test Threshold
Crustacea	Daphnia magna	EC <sub>50</sub> (48-hr): 168 mg/l (estimated)
Fish	Oncorhynchus mykiss	LC <sub>50</sub> (96-hr): 78 mg/l (estimated)
Fish	Melanotaenia fluviatilis larvae	LC <sub>50</sub> (96-hr) 1,820 µg/l (estimated)

\*Estimates for product may be based on additional component data not shown

**Persistence and degradability** No data available.

**Bioaccumulative potential** Potential to bio-accumulate is expected to be low

**Mobility in soil** No data available. This class of chemical mixture is expected to exhibit limited mobility in saturated and semi-saturated soils. Due to oleophilic natural of a primary component, some level of phase separation can be expected with the oleophilic recoverable as a LNAPL at the piezometric surface of the water table

**Other adverse effects** No other adverse environmental effects known (*i.e. ozone depleting substance, tropospheric ozone precursor, greenhouse gas emission, endocrine disruptor or other deleterious environmental effect*)

## 13. Disposal considerations

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations

**Hazardous waste code** As packaged, this product meets criteria defining RCRA ignitable (D001) hazardous waste when disposed. (40 CFR Part 261, Subpart C). Before selecting disposal method, ensure that the waste materials have been properly assessed and, as necessary, tested to confirm regulatory status and all applicable waste codes.

**Waste from residues/unused product** Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner. (see: Disposal instructions).

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may contain product residue, follow label warnings even after container is emptied.

## 14. Transport information

### USDOT

**UN number** UN1223

**UN proper shipping name** Kerosene, COMBUSTIBLE LIQUID, n.o.s

**Transport hazard class(es)**

**Class** 3

**Subsidiary risk** -

**Packaging group** III

**Special precautions for user** Read safety instructions, SDS, and emergency procedures before handling.

**Marine pollutant** No



# SAFETY DATA SHEET

## Additional Information

**Non-bulk packages (less than or equal to 119 gal) are not regulated as hazardous materials.**

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code This product is periodically transported in bulk containers.

DOT Label / Placard – Bulk Packaging Only



## 15. Regulatory information

### US federal regulations

SARA 302 Extremely hazardous substance Not listed.

SARA 304 Emergency release notification Not listed.

### SARA 311/312 Hazard Categories

Immediate Hazard - Yes

Delayed Hazard – No

Fire Hazard – Yes

Pressure Hazard – No

Reactivity Hazard – No

SARA 313 (TRI reporting) Not listed.

### California Proposition 65



**WARNING:** This product can expose you to the chemicals petroleum, naphthalene which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

## 16. Other information, including date of preparation or last revision

Issue date	5/27/2015
Revision date	4/5/2019, 3/31/2020
Version #	3
HMIS® ratings	Health: 1 Flammability: 2 Physical hazard: 0



# SAFETY DATA SHEET

HEALTH	1
FLAMMABILITY	2
REACTIVITY	0
PERSONAL PROTECTION	<input type="checkbox"/>

## NFPA ratings

Health: 1  
Flammability: 2  
Instability: 0



## Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, and have been obtained from resources believed to be reliable. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal, and release and is not to be considered a warranty or quality specification. The information related only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified by the text.

## Revision information

4/5/2019 Remove carcinogenicity category 3 – Not identified in SDS source material; Naphthalene is identified IARC carcinogen but in product at under 0.01% by weight. Added chronic aquatic hazard – Category 3 Calculated threshold not exceeded. General format update; Refine composition table, amend physical data; Update toxicology thresholds and environmental fate information; Text clarification amendments Sections 5,6,8,9 and 12. PPE recommendation updated; California Proposition 65 notice; HMIS and NFPA pictograms added.

3/31/2020 Updated product toxicity table, new logo, format updates; Add qualifier for DOT shipping name exemption if shipped non-bulk per 49 CFR 173.150(f). Amend proper shipping name to correspond with raw stock product. Change Proposition 65 notice to include naphthalene warning. Ecological toxicity table data updated.