



PHYSICAL PROPERTIES

Appearance: Milky White Liquid

Specific Gravity: 1.03

Odor: Characteristic

Ph (Conc.): 7-8

Flash Point: >200°F

PACKAGING

4X1 gal, 5 gal, 55 gal

Tile Floor Sealer

BASE COAT

ABOUT THIS PRODUCT

Tile Floor Sealer is designed to be used as a base coat which will fill-in tile imperfections and insure the bonding process of re-coating tile floors. Tile Floor Sealer is a blend of acrylic polymers and leveling agents. It is formulated to provide a more secure bond to tile and increase floor finish coverage rate.

WARNING: WET FLOORS ARE SLIPPERY

Use proper caution and display warning placards anytime floors are wet. This product is not recommended for exterior use or use on interior floors that are subject to standing water or wet conditions.

DIRECTIONS

1. Thoroughly clean the floor and remove all old wax or finish using a solution of a concentrated wax and finish stripper. Pay particular attention to corners and baseboards to ensure that all old coatings have been removed.
2. Scrub rinse well with clear water; pick up with a wet vac or mop and allow to dry.
3. Apply Tile Floor Sealer using a rayon mop or gravity fed applicator.
4. If floor has a uniform luster, sufficient sealer has been applied. If not, a second coat should be applied in the same manner. Be sure the previous coat is "tack free" before applying floor finish.
5. Apply 5 coats of floor finish.

COVERAGE: 800 sq. ft. per gallon

RECOMMENDED USES: This product is recommended for finishing and maintaining asphalt tile, vinyl, vinyl composition, rubber tile and linoleum.

PRECAUTIONARY STATEMENTS

Prevention: Wash hands and exposed skin thoroughly after handling. Wear eye protection/face protection. If skin irritation occurs: Get medical advice/attention. **Response:** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

CUI Solutions, Inc.

1841 VERNON ST. | N. KANSAS CITY, MO 64116 | 816-471-3602
FAX: 816-474-3302 | WWW.CUISOLUTIONS.COM