



# Wood Seal WB

## WATER-BASED WOOD FINISH



### PHYSICAL PROPERTIES

**Appearance:** Milky White Liquid

**Specific Gravity:** 1.03

**Odor:** Characteristic

**Ph (Conc.):** 7-8

**Flash Point:** >200°F.

### PACKAGING

2x2.5, 4X1 gal, 5 gal

### ABOUT THIS PRODUCT

Wood Seal WB is a cross-linked, water-based coating, based on the latest polymer technology. It is non yellowing, has low odor, is non flammable and meets current V.O.C. regs. Wood Seal WB can be applied over existing solvent based finishes.

**Important Notes:** Do not use over floor finishes, shellac, lacquer, or two part water based epoxy coatings.

#### SURFACE PREPARATION

**Previously Finished Floors:** 1. Dust mop to remove all loose debris. 2. Remove all gum and tape. 3. Apply Super Clean, Gym Floor Cleaner in a 10'x10' area. Scrub surface with a standard 175 rpm buffer equipped with a 120 grit sanding screen. A conventional floor pad should be used between the screen and buffer drive block. Do not overwet the floor. Scrub surface then immediately pick up the solution with a wet-vac or auto scrubber.

**Newly Sanded Floors:** 1. Newly sanded floors should have one coat of solvent based wood finish applied to them before using a water-based finish. 2. After the coat of solvent based finish is applied and has cured for more than 48 hours, the preparation steps listed in Part A may be performed.

### DIRECTIONS

1. Do not apply when temperature is over 90° or when humidity is over 80%.
2. Before applying Wood Seal WB, close all doors and windows and shut down air-moving systems.
3. Do not apply more than two coats in one day.
4. Apply Wood Seal WB using a weighted application bar, lambswool applicator or mechanical applicator. Apply with the grain of the wood. Allow to dry until no tackiness is present before applying additional coats. If more than 24 hours has expired, a light screening process will need to be performed if additional coats are desired. Two coats of Wood Seal WB will give you a high level performance when applied over an existing solvent-based finish.
5. After the last coat has been applied, allow to dry overnight with some ventilation before light foot traffic and 48 hours before heavy foot traffic.

#### MAINTENANCE:

1. Dust mop at least daily, with a mop treated with a water-based dust mop treatment. Be sure to treat the mop at least 24 hrs. before use.
2. Damp mop at least weekly with Neutral Cleaner.
3. To restore glow use Red Restorer according to label instructions and burnish with a high speed buffer.

### PRECAUTIONARY STATEMENTS

**Prevention:** Wash hands and exposed skin thoroughly after handling. Wear eye protection/face protection. **Response:** If skin irritation occurs: Get medical advice/attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.