



## PHYSICAL PROPERTIES

**Appearance:** Green Liquid

**Specific Gravity:** 1.02

**Odor:** Butyl

**Ph (Conc.):** 11.5-12.5

**Flash Point:** >212°F (100°C).

## PACKAGING

4x1 Gallon

# Zinc-Free Floor Finish

## HIGH GLOSS

## ABOUT THIS PRODUCT

Earth Worx Floor Finish is Zinc Free, produces a high gloss, is easy to apply, and environmentally preferred. Earth Worx Floor Finish is responsive to high speed burnishing and extremely durable. It can be used on all resilient floors-vinyl asbestos, asphalt tile, vinyl sheet and tile, rubber, reinforced vinyl, and linoleum.

## DIRECTIONS

1. Clear the area to be finished of all movable objects.
  2. Sweep the floor clean of loose dirt and debris.
  3. Apply stripper and remove all old wax and floor finish. Repeat if necessary.
  4. Rinse the floor as thoroughly as possible and let dry.
  5. Work with clean equipment and mop on a thin coat of finish. Allow to dry thoroughly (at least 30–45 minutes) before applying another coat.
  6. A minimum base of 4–5 coats is required before burnishing.
- Sweep daily with a dust mop or cloth. Clean with a neutral pH cleaner with a mop bucket or automatic scrubber.
- Pad Suggestions: Natural fiber pads are preferred for burnishing. A tan, beige, or light blue synthetic pad can also be used.

## PRECAUTIONARY STATEMENTS

Prevention: Wash hands and exposed skin thoroughly after handling. Wear eye protection/face protection. Response: If skin irritation occurs: Get medical advice/attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

**CUI Solutions, Inc.**

1841 VERNON ST. | N. KANSAS CITY, MO 64116 | 816-471-3602

FAX: 816-474-3302 | [WWW.CUISOLUTIONS.COM](http://WWW.CUISOLUTIONS.COM)