



## **PHYSICAL PROPERTIES**

Appearance: Light Yellow Liquid

Specific Gravity: 1.04
Odor: Characteristic
Ph (Conc.): 11-12

Flash Point: >212°F (100°C)

## **PACKAGING**

5 gal pail, 55 gal drum

# **Asphalt Release**

## **ASPHALT RELSEASE AGENT**

## **ABOUT THIS PRODUCT**

Asphalt Release is a solvent baseed asphalt release agent that prevents the adhesion of asphalt to truck beds and other asphalt handling equipment. This water mixable agent is designed to provide clean, rapid and easy separation of bituminous (asphalt) materials from beds of dump trucks and haul trucks.

Asphalt Release performs well on steel, aluminum and rubber surfaces. The product was designed to aggressively adhere to vertical surfaces such as truck boxes, tailgates, drag slats, pavers and even hand tools. Once Asphalt Release is applied to the truck bed, a micro-thin film spreads out across the truck bed. This film creates a negative electrostatic charge on both the surface of the truck bed and the asphalt. This causes electrostatic repulsions preventing the asphalt from sticking to the surface of the truck bed.

Usually three hauls can be made before another application is required.

#### **DIRECTIONS**

Asphalt Release can be applied directly to the surface to be protected as a coarse spray or foam.

Dilute 1:20 parts or greater with water.

## **PRECAUTIONARY STATEMENTS**

**Prevention:** Wear eye protection/face protection. Wash hands and exposed skin thoroughly after handling. Wear protective gloves.

**Response:** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor/medical professional. IF ON SKIN: Wash with plenty of water for at least 15 minutes. Specific treatment (see section 4 on the Safety Data Sheet). If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.