



Float Solv

LIFT STATION DEGREASER



PHYSICAL PROPERTIES

Appearance: Colorless to light yellow Liquid

Specific Gravity: 0.8 (water=1)

Odor: Characteristic.

Ph (Conc.): N/A

Flash Point: Closed cup: 100°F to 140°F (38°C to 60°C)

PACKAGING

5 gal pail, 55 gal drum

ABOUT THIS PRODUCT

Float Solv is a unique blend of Orthobenzene and Peptizing agents specifically designed for the maintenance of lift stations and grease traps. The properties of this chemical allow it to float and suspend on "top" of the water. As the control valves and floats inside a lift station raise and lower the level of sewage, Float Solv stays on top cleaning and degreasing the side walls and controls of the lift station.

Float Solv is harmless to all rotors, seals, "O" rings and control valves, attacking only the undesirable grease and sludge that accumulates in these areas. It may be necessary to clean and degrease the area before applying Float Solv as a maintainer.

Consult with your representative for proper application and dosage. Cleans and Degreases walls and mechanisms automatically. Use on sides of tanks, in sewer lines, ect. Easy to use - just pour in. Will not freeze.

FOR USE IN: Lift Stations, Waste Treatment Plants, Wet Wells, Digesters And Water Treatment Plants.

DIRECTIONS

For Grease Traps: To keep clean, fresh smelling and free flowing, add enough product to maintain a 1 to 3 inch layer above the water level. (Two quarts will cover 60 square inches at a depth of 2 inches.) If trap is heavily loaded with grease, it must be cleaned out manually before adding this product.

For Sewage Plants: Add to lift station. Depending on quantity of accumulated scum, grease and oils; Pour in enough product to maintain a blanket layer of 1 to 3 inches. It takes approximately one gallon of product per square foot.

PRECAUTIONARY STATEMENTS

Prevention: Keep away from heat/sparks/open flames/ hot surfaces. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting/ equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/ eye protection/ face protection.

Response: Wash hands and exposed skin thoroughly after handling. Obtain special instruction before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction. Specific treatment: see section 4 on the Safety Data Sheet. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention. IF INHALED: Remove person to fresh air and keep comfortable breathing. Call a POISON CENTER/doctor/medical professional if you feel unwell. IF SWALLOWED: Immediately call a POISON CENTER/doctor/medical professional. Do NOT induce vomiting. **Storage:** Store in a well-ventilated place. Keep cool. Store locked up. Keep tightly closed.

Disposal: Dispose of contents/container in accordance with local/regional/national/ international regulations.